

## Accu-Riveting Tool Type NSG

### Product Description

Electro-mechanic riveting tool for installation of fischer Undercut Anchor FZP-N

### Advantages

- Cableless
- High pulling strength
- High speed setting
- Mandrel container for spent mandrels

### Technical Details (range of delivery)

- Delivery includes metal carrying case, battery and quick battery charger
- On demand a second battery is included
- Nosepiece 17/32 in working position, further nosepieces 17/24, 17/29, 17/32 in magazine

### Operation Steps

1. Insert FZP-N Anchor into the nosepiece and hold it in place.
2. Lead FZP-N Anchor through hole of attachment part (bracket) into the undercut hole.
3. Hold the tool vertical to panel surface and lead it downwards with a little load in direction anchor-drill-hole axis.
4. Start the tool and keep the downwards pressure constantly until tearing of mandrel.



### Technical Details

Dimensions (Metal carrying case)	345 x 275 x 90 mm ( B x T X H)
Total weight (including second battery)	4.7 kg
<b>Setting Tool</b>	
Weight (setting tool)	2.0 kg (incl. battery)
Total stroke	20 mm
Operating voltage	12 Volt DC
Pulling strength	8,500 N
<b>Battery</b>	
Nominal Voltage	14,4 V
Nominal Capacity	1,3 Ah
Cell composition	Li-Ion battery, No memory effect.
Weight	0,35 kg
<b>Quick battery charger</b>	
Input voltage	230V/50 Hz (optional 115V/60Hz)
Charging time	approx. 1-1.5 hour
Weight	0.6 kg
Costs / Configuration	on request

### ACT Service

fischerwerke GmbH & Co. KG

Weinhalde 14-18 · 72178 Waldachtal

Phone +49 74 43 12-45 53 · Fax +49 74 43 12-49 07

act@fischer.de · www.fischer.de